

# 5MP IP AI+ FULL COLOR WARM LIGHT MINI DOME POE CAMERA

Model #: IPC-EDFR5MP-AI-S-WL



## Features:

- 5MP 2592(H)×1944(V)
  - AI FULL Color Night Warm Light & IR
  - H.265+ H.264+ Ready, H.264. MJPEG
  - 3D DNR, BLC, WDR, ICR, SD Card up to 256GB
  - Light Range: Up to 100 ft
  - Dual Video Streams
  - IP66 Rating
  - Metal housing & Bracket
  - FULL COLOR Day/Night
- 
- AI Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Sound Detection, Crossing Count

For more information please contact a DSS Sales Representative

Toll Free: 1.888.467.8812 · Fax: 1.609.431.0932 · Email: [sales@dss-cctv.com](mailto:sales@dss-cctv.com)  
[www.dssdepot.com](http://www.dssdepot.com)

# Technical Specifications


<b>Model No.</b>	IPC-EDFR5MP-AI-S-WL
<b>Camera</b>	
Image sensor	1/2.7" Progressive CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/10,000s
Lens	2.8mm @F2.0 Horizontal: 110°, Vertical: 57.8°, Diagonal: 131.6°
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Built-in Mic	Support
<b>Compression Standard</b>	
Video compression	H.264 / MJPEG / H.264+/H.265+
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual streams	Support
<b>Image</b>	
Max. Image Resolution	5MP 2880(H)×1620(V)
Frame rate	60Hz: (1~30fps)5MP(2592×1944),4MP(2592×1520) 3MP(2048×1520),1080P(1920×1080) 960P(1280×960), 720P(1280×720)
Image settings	Rotate Mode, Saturation, Brightness, Contrast Sharpness adjustable by client software or web browse
BLC	Yes, zone configurable
ROI Codec	Support
<b>Network</b>	
Network storage	NAS (Support NFS,SMB/CIFS), ANR
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP,PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Interoperability	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Security	User Authentication, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
Web Browser	IE 7, IE 8, IE 9
P2P Connection	Built in
Mobile App	RXCAMVIEW Android/iPhone
<b>General</b>	
Operating conditions	(-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5W (Max 7W with IR cut filter on)
Weather proof rating	IP66
IR range	Up to 100 ft
Warm Light Range	Up to 100 ft
Dimension	3.9" x 3.5" x 3.9"
Weight	1.1 lbs

We reserve the right to modify product design and specification without notice and without incurring any obligation

**For more information please contact a DSS Sales Representative**

**Toll Free: 1.888.467.8812 · Fax: 1.609.431.0932 · Email: [sales@dss-cctv.com](mailto:sales@dss-cctv.com)**

[www.dssdepot.com](http://www.dssdepot.com)



We reserve the right to modify product design and specification without notice and without incurring any obligation

**For more information please contact a DSS Sales Representative**

Toll Free: 1.888.467.8812 · Fax: 1.609.431.0932 · Email: [sales@dss-cctv.com](mailto:sales@dss-cctv.com)

[www.dssdepot.com](http://www.dssdepot.com)