

# 1080P 2 Wireless Battery Bullet IP Camera Package

Model #: IP-BFR2MP2PK-W



## Features

- 1x 6CH 1080P Wireless NVR with 1TB
- 2x 1080P Wireless Battery IP Camera
- Up to 600 Ft Wireless Range
- Thermo-Sense Motion Sensor
- Rechargeable Battery up to 6 Months
- Two Way Audio, IP66 Weather Proof
- 70 Ft Infrared Night Vision

# Technical Specifications

<b>Model No.</b>	IP-BFR2MP2PK-W
<b>Wireless Battery IP Camera Specification</b>	
<b>Camera</b>	
Image sensor	1/2.7" 2MP progressive scan CMOS
Min. illumination	0.05 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/10,000s
Lens	2.8mm@F2.0, angle of view: 92.2°
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
<b>Compression Standard</b>	
Video compression	H.264 / MJPEG / H.264+
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual streams	Support
<b>Image</b>	
Max. Image Resolution	1920x1080 2MP
Frame rate	30fps (1920 × 1080), 30fps (1280 x 720)
Image settings	Rotate Mode, Saturation, Brightness, Contrast Sharpness
BLC	Yes, zone configurable
ROI Codec	Support
<b>Function</b>	
Motion Angle	Up to 115°
Motion Distance	Up to 70 Feet
Motion PIR	Thermo-Sense Motion Detection
Battery Capacity	2900mAh/ea
Battery Life	Up to 350 charges
Power Consumption	420mA(Activate) / 400μA (Sleep)
Warnings	Low Battery Warnings via app notifications
<b>Interface</b>	
Power Source	DC 4.2V±10%
Two way audio	Support
Speaker	Built-in, Weather Proof
Mic	Built-in, Weather Proof
<b>Wireless</b>	
Wireless Standards	DSSS (Direct-Sequence Spread Spectrum)
Wireless Distance	Up to 600 Ft with a clear line-of-site
<b>General</b>	
Operating conditions	(-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	DC 4.2V±10%
Power consumption	Max. 1.8W
Weather proof rating	IP66
Housing	Metal
IR range	6 IRs, Up to 70 Ft
Dimension	5.4" x 2.9" x 3.5"
Weight	1.1 lbs

## Wireless NVR Specification

### Video/Audio input

Video compression	H.264
IP Video Input	6-ch
Incoming Bandwidth	32 Mbps

### Video /Audio output

HDMI output	1-ch, resolution: 1920 x 1080P /60 Hz ,1600 x 1200 /60 Hz,
Video spot output	N/A
Encoding resolution	1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Frame rate	60 fps (max 20 fps each)
Video bit rate	32 Kbps ~ 8192 Kbps, or user defined (Max. 8192 Kbps)
Dual-stream	Support   (Sub-stream at CIF / QCIF: 30fps)
Stream type	Video, Video & Audio
Playback resolution	1080P / UXGA / 720P / 4CIF / VGA / DCIF / 2CIF / CIF / QCIF
Synchronous playback	6-ch

### Hard Disk

SATA	1 SATA interfaces 2.5inch HDD
Capacity	Up to 6TB capacity

### External interface

Network interface	1 RJ-45 10 /100 Mbps WAN interface; 3 RJ-45 10 / 100M LAN interfaces.
Serial interface	N/A
USB interface	3 USB2.0
Alarm in/out	N/A

### Wireless-WiFi

Frequency Band	DSSS (Direct-Sequence Spread Spectrum)
Antenna Structure	2 x2 MIMO
Transmission Rate	300 Mbps
Transmission Standard	IEEE 802.1b/g/n
Network Protocol	IPv6, UPnP, SNMP, NTP, SADP, DDNS, SMTP, NFS, iSCSI.
Remote connection	128

### General

Power supply	12 VDC
Consumption	≤12 W
Working temperature	14°F - 131°F
Working humidity	10% ~ 90%
Chassis	Mini Stand
Dimensions	87 × 87 × 157 mm
Weight	< 1.2lb without HDD



We reserve the right to modify product design and specification without notice and without incurring any obligation

**For more information please contact a DSS Sales Representative**

**Toll Free: 1.888.467.8812 · Fax: 1.609.431.0932 · Email: [sales@dss-cctv.com](mailto:sales@dss-cctv.com)**

**[www.dss-cctv.com](http://www.dss-cctv.com)**